

THE ABC'S OF GASES IN THE INDUSTRY

Ammonia: NH_3	n-Butane*: C_4H_{10}
Colorless gas with a pungent suffocating odor STEL: 35 ppm TWA: 50 ppm IDLH: 300 ppm LEL: 15% by volume Ionization Potential: 10.18 eV • Fertilizer Plants • Fish & Meat Packing Plants • Industrial Refrigeration and Cold Storage • Semiconductor Industry • Water and Wastewater Treatment Plants • Munitions <i>Refer to AP-201 for further information</i>	Colorless gas with a gasoline-like odor STEL: 1 ppm TWA: OSHA 5 ppm LEL: 1.6% by volume • Aerosol Propellant Filling Docks • Feed stock for Chemical Processes • Storage Tanks and Filling Docks
Benzene: C_6H_6	Carbon Dioxide: CO_2
Colorless liquid with aromatic odor STEL: 2.5 ppm TWA: 0.5 ppm LEL: 1.2% • Refineries • Oil & Gas Distribution • Feed Stock for Chemical Production • Solvent Distribution Centers • Gas Stations	Colorless, odorless gas STEL: 30,000 ppm TWA: OSHA 5000 ppm IDLH: 40,000 ppm • Breweries and Wineries • Carbonated Beverage Bottling Plants • Dry Ice Plants, Food Processing Plants, Fruit Storage and Ripening Chambers • Greenhouses, Indoor Air Quality Studies, and Ventilation Control • Mushroom Farms Stack Gas • Oil Well Injection

Carbon Monoxide: CO	Chlorine: Cl ₂
Colorless, odorless gas - most abundant toxic gas STEL: ppm TWA: OSHA 50 ppm LEL: 12.5% IDLH: 1200 ppm • Furnaces • Gasoline Generators/Engines • Grain Storage Silos • Lumber Drying Kilns • Mining and Metals • Parking Garages	Green-yellow gas with a pungent, irritating odor STEL: 0.3 ppm TWA: OSHA 0.1 ppm IDLH: 5 ppm • Mining & Metals Industry • Nuclear Reactors • Pulp & Paper Mills • PVC Plastics Manufacturing • Semiconductor Water Etching Facilities • Swimming Pool Chlorinization Plants • Water Treatment Plants • Chlorine Gas Manufacturing
n-Hexane*: C ₆ H ₁₄	Hydrogen*: H ₂
Colorless liquid with a gasoline-like odor TWA: OSHA 500 ppm LEL: 1.1% IDLH: 1100 ppm • Electric Generation • Gas Stations • Peanut Oil Extraction Plants • Solvent Distribution Centers	Colorless gas No exposure limits – Simple asphyxiant • Battery Charging Stations • Semiconductor Plants for Water Furnaces • Underground Vaults Containing Transformers • Vegetable Oil Hydrogenation Plants
Hydrogen Cyanide: HCN	Hydrogen Sulfide: H ₂ S
Colorless gas with a bitter, almond-like odor TWA: OSHA 10 ppm LEL: 5.6% IDLH: 50 ppm • Plating and Mining • Nylon Manufacturing	Colorless gas with a strong odor of rotten eggs TWA: OSHA 20 ppm LEL: 4.0% IDLH: 100 ppm • Leather Tanneries and Paper Mills • Mining and Metals Industry • Oil Fields and Refineries • Sewage Treatment Plants • Sewer Maintenance
Methane: CH ₄	Nitric Oxide: NO
Colorless, odorless gas – odorized with mercaptans Primary component of natural gas No exposure limits – Simple asphyxiant LEL: 5% • Oil & Gas Distribution & Refining • Mining Industry	Colorless gas TWA: NIOSH/OSHA 25 ppm IDLH: 100 ppm • Semiconductor Plants • Mining

Nitrogen Dioxide: NO ₂	Oxygen Deficiency: O ₂
Reddish-brown with a pungent odor STEL: 1 ppm TWA: OSHA 5 ppm IDLH: 20 ppm - Boilers and Furnaces - Diesel Emissions - Semiconductor Plants - Mining Industry	Colorless, odorless gas - Cargo Holds and Storage Tanks - Grain Storage Silos With Inerted Atmospheres - Liquid Nitrogen Storage - LN2 Cooled Laser Facilities - LN2 Cooled Telescope - Sewer Maintenance - Sewer Treatment Facilities - Underground Vaults (Utilities)
Propane*: C ₃ H ₈	Sulfur Dioxide: SO ₂
Colorless, odorless gas TWA: OSHA 1000 ppm LEL: 2.1% IDLH: 2100 ppm (LEL) - Aerosol Propellant Filling Lines - Feed stock for various Chemical Processes - Propane-powered Forklifts - Storage Tanks & Filling Docks	Colorless gas with a pungent odor STEL: 5 ppm TWA: NIOSH 2 ppm IDLH: 100 ppm - Circuit Board Etching - Diesel Emissions - Paper Mills - Sulfur Processing Plants (SO₂) - Water Treatment
Volatile Organic Compounds (VOCs) Refer to the NIOSH Pocket Guide for specific chemical hazards	
- Airline Maintenance Facilities (Jet fuel - refer to AP-200) - Consultant Engineering - Leaking Underground Storage Tanks - Petrochemical Manufacturing - Aerospace Manufacturing - Automotive Manufacturing (paint booths—refer to AP-204) - High Tech Electronics Manufacturing - Pharmaceutical Manufacturing - Chemical Printed Circuit Board Fabrication - Transportation (spills from tankers, cars) - Printing (lithography and flexography) - Fiberglass reinforced plastics (refer to AP-205) - Hazardous Waste Facilities	- Coating (cans, coils, and fabrics) - Forest products - Component manufacturing (parts spray-painting, resin components, adhesive components, misc. metalworking) - Regulatory agencies (OSHA, EPA, DOT) - Military (base closures) - Marine Chemists (ships and barges) - Emergency Response/HazMat teams (refer to AP-203) - Fire Departments: Arson Investigation - TSD (Treatment, Storage & Disposal) - Municipal/Public Works - Federal, State and Municipalities - Coke oven off gases (refer to AP-206)

*Denotes Combustible Gas