

TF Foam Discharge Head

Application

Depending on the hazard, various low expansion foam agents, such as protein, fluoroprotein, AFFF, Alcohol Resistant AFFF, and Class A foam concentrates can be used with the TF discharge head. Typical applications include dike protection, pump pit areas, and as ground sweep nozzles for truck loading racks.

Description


The brass TF foam discharge head is designed to discharge foam in a spray pattern. These air-aspirated directional spray heads can be mounted in any position between horizontal to vertical.

The head attaches to foam solution piping with the 1/2-14 NPT male threaded connector. Maximum diameter is 3 3/4 in. (95 mm) and height is 4 1/2 in. (114 mm).

Approvals and Listings

The TF foam discharge head is Underwriters Laboratories (UL) Listed with various foam agents.


Coverage Patterns



Ordering Information

Part No.	Description	K-Factor	Approximate Shipping Weight	
			Lb	(kg)
702740	TF-18 Foam Discharge Head	1.8	2	(0.9)
702741	TF-29 Foam Discharge Head	2.9	2	(0.9)
702742	TF-39 Foam Discharge Head	3.9	2	(0.9)
702743	TF-57 Foam Discharge Head	5.7	2	(0.9)
702744	TF-74 Foam Discharge Head	7.4	2	(0.9)

TF Foam Discharge Heads Flow Characteristics



Note: The converted metric values in this document are provided for dimensional reference only and do not reflect an actual measurement.

CHEMGUARD and the product names listed in this material are marks and/or registered marks. Unauthorized use is strictly prohibited.